

The Onity OS700 hotel in-room safe series features contactless RFID technology, following the latest market trends and demands. Operated by the room entry keycard, it is very easy to use and functional.

Combined with the proven reliability Onity solutions are known for, OS700 series safes are the ideal solution for properties looking to offer high security for their guests' belongings.

Features

- Sleek modern design
- User friendly, works approaching card to reader
- Reading technology: contactless RFID (ISO14443A, 14443B part 4, NFC)
- Supports MIFARE® Classic/EV1, Plus, Ultralight and Ultralight C cards
- Multiple opening devices available: cards, wristbands, keychains, etc.
- Non-volatile memory: records last 500 operations, including date, time and user
- Each new guest card overrides any previous ones
- Compatible with Onity OnPortal™, HT24W and HT22 stand alone electronic locking systems
- Mechanical key override for emergency openings, single key for all safes or individual keys
- 2 solid steel, anti-drill bolts
- Fixing points
- Interior carpet
- Interior shelf (Mini size only)
- Low battery consumption
- Works with 4 AA standard batteries
- LEDs indicate status, including low battery

Options

- Finish: Black (standard) or Ivory
- Hand: Right (standard) or Left handed *
- Rental mode at check-in
- Power outlet

Portable Programmer Unit

- Emergency openings
- Password protected
- Downloads audit trail (last 500 operations)



Dimensions

Mini size

External Dimensions:	250 x 350 x 250 mm (H x W x D) **
Volume:	15.3 L
Net Weight:	10.8 Kg
Door Opening:	205 x 250 mm (H x W)

Laptop size (standard)

External Dimensions:	200 x 420 x 370 mm (H x W x D) **
Volume:	22.7 L
Net Weight:	9.7 Kg
Door Opening:	160 x 333 mm (H x W)

17" Laptop size

External Dimensions:	204 x 508 x 370 mm (H x W x D) **
Volume:	31.2 L
Net Weight:	14.5 Kg
Door Opening:	160 x 415 mm (H x W)

Certifications

- RED Directive 2014/53/EU
- RoHS Directive 2011/65/EU

* Left hand available for Laptop and 17" Laptop sizes

** Depth indicates box dimensions, reader (20 mm) is not included