


Onity presents **solution** AB3, a range of silent minibars designed specifically for hospitality market needs.

- ☐ **Ecological:** they comply with high quality and environmental requirements.
- ☐ **Silent** operation, absorption technology cooling system, featuring no moving parts.
- ☐ **Flexibility** thanks to easily reversible door.
- ☐ **Different sizes:** **solution** AB3 minibars are available in two sizes, 30L and 40L.
- ☐ Low consumption LED light.
- ☐ Concealed thermal regulator.
- ☐ Intelligent automatic defrosting system controlled by IC chip.
- ☐ Foaming with cyclopentane (C₅H₁₀), CFC-free thermal insulation with ultra cooling efficiency.
- ☐ Easy-opening door knob.
- ☐ Antibacterial removable soft PVC door seal.
- ☐ HIPS antibacterial liner to dispel interior odor.
- ☐ **Options:** A range of optional features is available to personalise the minibar to meet customers' needs.

IMPORTANT: Ventilation

The cooling unit requires ventilation for an optimal running of the minibar, therefore it is recommended to leave a minimum space of **5 cm** around it.





Certifications

- ☐ 2014/30/EU (EMC)
- ☐ 2014/35/EU (LV)
- ☐ EU/2019/2019 (EcoDesign)
- ☐ 2011/65/EU (RoHS)



Technical Specifications

Model	Solution AB3 30	Solution AB3 40
Volume Available	29 L	39 L
Colour	Black	Black
Dimensions (H x W x D)	480 x 400 x 420 mm	550 x 400 x 440 mm
Nominal Power	65 Watt	65 Watt
Power Supply	220-240 V ~ 50/60 Hz	220-240 V ~ 50/60 Hz
Energy Consumption	0.521 kWh / 24 h 190 kWh / year	0.523 kWh / 24 h 191 kWh / year
EEL (Energy Efficiency Index)	249.5	249.1
Energy Efficiency Class	G	G
Climate Class	N	N
Airborne Acoustical Noise Emission Class	A	A
Net Weight	13.2 Kg	14.8 Kg
Thermostat Type	Electronic	Electronic
Power Cable Length	1.6 m	1.6 m
Temperature Interval	0 to 8 °C	0 to 8 °C
Internal Light	Yes (LED type)	Yes (LED type)
Shelves	1 tempered glass + 2 door racks	2 tempered glass + 2 door racks
Door Type	Solid	Solid
Sliding Hinge for Cabinet	Yes (optional)	Yes (optional)
Lock with Key	Yes (optional)	Yes (optional)




Onity presents **solution** AB3 Glass, a range of silent minibars with glass door, designed specifically for hospitality market needs.

- ❑ **Ecological:** they comply with high quality and environmental requirements.
- ❑ **Silent** operation, absorption technology cooling system, featuring no moving parts.
- ❑ **Flexibility** thanks to easily reversible door.
- ❑ **Different sizes:** **solution** AB3 Glass minibars are available in two sizes, 30 L and 40 L.
- ❑ Low consumption LED light.
- ❑ Concealed thermal regulator.
- ❑ Intelligent automatic defrosting system controlled by IC chip.
- ❑ Foaming with cyclopentane (C₅H₁₀), CFC-free thermal insulation with ultra cooling efficiency.
- ❑ Easy-opening door knob.
- ❑ Antibacterial removable soft PVC door seal.
- ❑ HIPS antibacterial liner to dispel interior odour.
- ❑ **Options:** A range of optional features is available to personalise the minibar to meet customers' needs.

IMPORTANT: Ventilation

The cooling unit requires ventilation for an optimal running of the minibar, therefore it is recommended to leave a minimum space of **5 cm** around it.



Certifications

- ❑ 2014/30/EU (EMC)
- ❑ 2014/35/EU (LV)
- ❑ EU/2019/2019 (EcoDesign)
- ❑ 2011/65/EU (RoHS)



Technical specifications

Model	Solution AB3 30-G	Solution AB3 40-G
Volume Available	29 L	39 L
Colour	Black	Black
Dimensions (H x W x D)	480 x 400 x 415 mm	550 x 400 x 435 mm
Nominal Power	65 Watt	65 Watt
Power Supply	220-240 V ~ 50/60 Hz	220-240 V ~ 50/60 Hz
Energy Consumption	0.619 kWh / 24 h 225.94 kWh / year	0.624 kWh / 24 h 228 kWh / year
EEl (Energy Efficiency Index)	296.4	297.2
Energy Efficiency Class	G	G
Climate Class	N	N
Airborne Acoustical Noise Emission Class	A	A
Net Weight	15.2 Kg	17 Kg
Thermostat Type	Electronic	Electronic
Power Cable Length	1.6 m	1.6 m
Temperature Interval	4 to 12 °C	4 to 12 °C
Internal Light	Yes (LED type)	Yes (LED type)
Shelves	1 tempered glass	2 tempered glass
Door Type	Glass	Glass
Sliding Hinge for Cabinet	No	No
Lock with Key	Yes (optional)	Yes (optional)

